HoldTight Solutions Inc. / HOLDTIGHT®102

MATERIAL SAFETY DATA SHEET (MSDS) ISO 11014-1 format (6 page ver.)

NOTE: Read and understand Material Safety Data Sheet (MSDS) before handling or disposing of product. Six (6) pages total.

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MATERIAL IDENTITY

Product Name:	HoldTight®	102 salt remover / flas	h rust inhibitor
Chemical Name and/or Family or Description:	HoldTight Solutions Inc. P.O. 27907, Houston, TX 77227,7907		NON-HAZARDOUS
Manufacturer's Name and Address:			NON-TOXIC BIO-DEGRADABLE
Telephone Numbers: FAX / email	713.266.9339 713.266.1022	800.319.8802 info@holdtight.com	NON-FLAMMABLE

2. COMPOSITION / INFORMATION ON INGREDIENTS

The criteria for listing components in the composition section are as follows: Chronic Hazards (Carcinogenic, Teratogenic, Mutagenic, Neurotoxic, and Sensitizers) are listed when present at 0.01% or greater: Acute Hazards are listed when present at 1.0% or greater and Non-Hazardous components are listed when present at 3.0% or greater.

Product and/or Component(s) Carcinogenic according to OSHA	IARC	NTP	OTHER	NONE	v
	—		—	-	<u>~</u>
Composition					
Chemical/Common Name				Range in	<u>1 %</u>
Proprietary Formulated Amine Compound				25.00	
Non- Hazardous Materials				75.00	

3. HAZARD IDENTIFICATION

EMERGENCY OVERVIEW

Appearance and Odor: clear liquid, mild ammonia odor

WARNING STATEMENT

CAUTION: may cause eye irritation

	<u>HMIS</u> Health: Flamma		1 0	Reactivi Special:		0 -	<u>NFPA</u> Health: Flammability:	1 0	Reactivity: Special:	0 -
POTEN	TIAL HEALTH EFFE	CTS								
Primary	Route of Exposure	•		ЕҮЕ <u>Х</u>	SKIN <u>X</u>	INHALATION X				
Effects	of Overexposure									
Acute:	Eyes:	May cau	use irritati	on, experi	ienced as	mild discomfort, an	nd seen as slight re	edness of	the eye.	
	Skin:	Prolong	ged contac		clothing	osorption of materia wetted with materia				
	Inhalation:	Vapors or mist, in excess of permissible concentrations, or in unusually high concentrations generated from spraying, heating the material or from exposure in poorly ventilated areas or confined spaces, may cause irritation of the nose and throat, headache, nausea, and drowsiness.								
	Ingestion:	May, in	very large	quantities	s, cause a	abdominal discomfo	ort, nausea, and dia	arrhea.		
	N.D Not Determir	ned	N.A N	ot Applicat	ole	N.T Not Tested	< - Less Than	> - Grea	iter Than	page 1 of 6

HoldTight®102	MSDS	issued Supersedes	06/01/2010 02/01/2010
Sensitization Properties:	This product is not expected to be a human sensitizer based on animal da	ata.	
Chronic:	No adverse effects anticipated.		
Medical Conditions Aggravated By Exposure:	Repeated skin contact may aggravate an existing dermatitis (skin condition	on).	
	Repeated overexposure may aggravate existing kidney disease.		
Other Remarks:	None		

4. FIRST AID MEASURES

Eyes:	Flush eyes with water several times. Hold eyelids apart while flushing to rinse entire surface of eye and lids with water. Get medical attention if irritation persists.
Skin:	Wash skin with soap and water. Get medical attention if skin irritation develops or persists.
Ingestion:	None considered necessary.
Inhalation:	If irritation, headache, nausea, or drowsiness occurs, remove to fresh air. Get medical attention if breathing becomes difficult or symptoms persist.
Other Instructions:	None

5. FIRE-FIGHTING MEASURES

Ignition Temp. Degrees F.:	N.D.	
Flash Point Degrees F. (Method):	>400⁰F (PMCC)	
Flammable Limits (%)	Lower: N.D.	Upper: <u>N.D.</u>

Recommended Fire Extinguishing Agents and Special Procedures:

According to NFPA Guide, use water spray, dry chemical, foam, or carbon dioxide. Water or foam may cause frothing. Use water to cool fire-exposed containers. If a leak or spill has not ignited, use water spray to disperse the vapors and to provide protection for person attempting to stop the leak.

Unusual or Explosive Hazards: None

6. ACCIDENTAL RELEASE MEASURES

Procedures in Case of Accidental Release, Breakage or Leakage:

Ventilate area to accelerate evaporation. Contain spill if possible. Avoid contact with skin, eyes or clothing. Low concentrations of the active ingredient can be degraded in a biological wastewater treatment system. Aquatic toxicity data indicates a very low order or negligible toxicity to aquatic organisms. It is, therefore, feasible to dispose of in a sanitary sewer with large amounts of water.

7. HANDLING AND STORAGE

Precautions to be taken in handling and storage: Minimum feasible handling temperatures should be maintained. Periods of exposure to high temperatures should be minimized. Water contamination should be avoided. Protect from freezing temperatures. Also see HMIS label on container

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Protective Equipment (Type)

Eye/Face Protection: Chemical - type goggles or face shield optional, but recommended to prevent eye contact.

Skin Protection: Workers should wash exposed skin several times daily with soap and water. Soiled work clothing should be laundered or dry-cleaned.

HoldTight®102 MSDS	issued Supersedes	06/01/2010 02/01/2010
--------------------	----------------------	--------------------------

Respiratory Protection:	Pursuant to standard industrial safety procedures, if vapor, mist or dust is generated in a contained space without fresh air ventilation, use respirator approved by MSHA or NIOSH as appropriate. See below for applicable permissible concentrations.
Ventilation:	Adequate to meet occupational exposure limits. General exhaust ventilation is acceptable. (See below)
Exposure Limit For Product:	25 mg/m ³ (TWA - ACGIH) undiluted; 1250 – 6250 mg/ m ³ diluted 50:1 to 250:1 per instructions for use

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and Odor:		clear liquid, light, pleasant odor
Boiling Point (Degrees F.):		212 ^o F
Percent VOC:		N.D.
Evaporation Rate (n-butyl acetate=1)		8.5
Specific Gravity (H ₂ 0=1):		1.0304
pH:		10.2
Solubility in Water:	1 00 %	
Vapor Pressure:		10.3 mmHg @: 100 ^o F
Viscosity:		2 cSt @ 77 ^o F
Freezing Point:		23 ⁰ F
Flash Point		>400°F (Method PMCC)
Weight		8.6 lbs/ gal; 3.9kg / gal

10. STABILITY AND REACTIVITY

This Material Reacts	
Violently With:	(If others is checked below, see comments for details)

Air	Water	Heat	Strong Oxidizers	Others	None of These
				v	

OCCUR

-

Comments: This material reacts with acids.

Products Evolved When Subjected to Heat or Combustion:

NONE

Hazardous Polymerizations:

DO NOT OCCUR <u>X</u>

11. TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION (ANIMAL TOXICITY DATA)

Median Lethal Dose (LD50 LC50) (Species)

Oral:> 10.0 - 25.0 g/kg (rat); slightly toxicInhalation:N.D.Dermal:> 50 g/kg (rabbit); practically non-toxic

Irritation Index, Estimation of Irritation (Species)

Skin:	believed to be 0.5-3.0/8.0 (rabbit); slightly irritating
Eyes:	believed to be 15-25/100 (rabbit); slightly irritating
Sensitization:	Negative (guinea pig)
Other:	Prolonged and repeated ingestion of compounds of active ingredient has caused kidney damage in
	laboratory animals.

12. ECOLOGICAL INFORMATION

The following information is compiled from various tests and studies on the proprietary compound in HoldTight® 102.

Aquatic toxicity data indicates negligible toxicity to aquatic organisms.

- The data show the compound is relatively non-toxic to bacteria, fathead minnows, and Daphnia magna.
- The "octanol water partition coefficient," (log P_{ow}) = -1.75 (Verschueren, 1983), indicates that the compound would not likely bioaccumulate in aquatic organisms.
- Biodegradation data show the compound biodegrades and will not persist in the environment. Increased rate of biodegradation by acclimation is
 expected in biological treatment systems that regularly process wastewater containing the compound.
- Environmental toxicity data indicate that optimal conditions will allow low level amounts of this compound to biodegrade (slowly); the residual (if any) will not have an appreciable impact on the environment.
- Due to negligible toxicity to aquatic life, product may be disposed of in sanitary sewers.
- This formulated compound is not a "Priority pollutant," under Sec. 307 of the Clean Water Act (CWA) nor is it a "Hazardous Substance" under Sec. 311 of that Act. And it is not regulated as a "Water Priority Chemical" under Title III, Sec. 313 of the Superfund Amendment and Reauthorization Act (SARA).

Contact manufacturer if additional ecological information is needed.

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHODS

This product has been evaluated for RCRA characteristics and does not meet the criteria of a hazardous waste if discarded in its purchased form. Under RCRA, it is the responsibility of the user of the product to determine at the time of disposal, whether the product meets RCRA criteria for hazardous waste. This is because product uses, transformations, mixtures, processes, etc. may render the resulting materials hazardous. However, when used as directed by manufacturer the product may be disposed of in a sanitary sewer system.

REMARKS: Biodegradation data indicates the product biodegrades and will not persist in the environment. An increased rate of biodegradation would be expected via acclimation in biological treatment systems that receive this product on a regular basis in wastewater.

14. TRANSPORT INFORMATION

TRANSPORTATION

DOT: PROPER SHIPPING NAME:	NOT REGULATED, US freight classification 55 for establishing freight rates
HAZARD CLASS: IDENTIFICATION NUMBER: LABEL REQUIRED:	N.A N.A. None
IMDG: PROPER SHIPPING NAME:	N.D.
IATA: PROPER SHIPPING NAME:	N.D.
TDG: PROPER SHIPPING NAME:	NOT REGULATED
HAZARD CLASS: IDENTIFICATION NUMBER: LABEL REQUIRED:	N.A. N.A. N.A.
15. REGULATORY INFORMAT	TION
A. Toxic Substances Control A	ct (TSCA):

This product and/or its components are listed on the TSCA Inventory

B.. SARA TITLE III

Title III Section 302/304 Extremely Hazardous Substance:

Component	CAS No.	Percent	RQ (lbs)	TPQ (lbs)
NONE				

CERCLA SECTION 102(a) Hazardous Substance

<u>Component</u> NONE	<u>CAS No.</u>	<u>Percent</u>	<u>RQ (lbs)</u>	
	11 Hazard Categori <u>Fire</u> <u>Pressu</u>	zation <u>re Reactive</u> Not App 	olicable	
Title III Section 313 Toxic Chemicals				
<u>Component</u> NONE	<u>CAS No.</u>	<u>Percent</u>		
WHMIS CLASSIFICATION				
Not regulated				
MICHIGAN CRITICAL MATERIALS				
No critical materials present.				
CALIFORNIA PROPOSITION 65				

This product does not contain materials which the State of California has found to cause cancer, birth defects, or other reproductive harm

16. OTHER INFORMATION

В.

C.

D.

THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE. IT IS PROVIDED INDEPENDENTLY OF ANY SALE OF THE PRODUCT FOR PURPOSE OF HAZARD COMMUNICATION AS PART OF HOLDTIGHT INC., PRODUCT SAFETY PROGRAM. IT IS NOT INTENDED TO CONSTITUTE PERFORMANCE INFORMATION CONCERNING THE PRODUCT.NO EXPRESS WARRANTY, OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE IS MADE WITH RESPECT TO THE PRODUCT OR THE INFORMATION CONTAINED HEREIN. DATA SHEETS ARE AVAILABLE FOR ALL HOLDTIGHT PRODUCTS. YOU ARE URGED TO OBTAIN DATA SHEETS FOR ALL HOLDTIGHT® PRODUCTS YOU BUY, PROCESS, USE OR DISTRIBUTE AND YOU ARE ENCOURAGED AND REQUESTED TO ADVISE THOSE WHO MAY COME IN CONTACT WITH SUCH PRODUCTS OF THE INFORMATION CONTAINED HEREIN.

TO DETERMINE APPLICABILITY OR EFFECT OF ANY LAW OR REGULATION WITH RESPECT TO THE PRODUCT, USER SHOULD CONSULT HIS LEGAL ADVISOR OR THE APPROPRIATE GOVERNMENT AGENCY. HOLDTIGHT® DOES NOT UNDERTAKE TO FURNISH ADVICE ON SUCH MATTERS.

Date: 04/01/01 Revised, Supersedes 07/14/99 Inquiries regarding MSDS should be directed to:

> HoldTight Solutions Inc. P.O. Box 27907 Houston, TX 77227.7907 Phone 713.266.9339 / 800.319.8802 Fax 713.266.1022 / 800.728.8861 email: msds@holdtight.com

PLEASE SEE BELOW FOR SHIPPING / PRODUCT LABEL

17. SHIPPING / PRODUCT LABEL

HoldTight®102

Read and understand Material Safety Data Sheet before handling or disposing of product.

INSTRUCTIONS FOR USE

In humid ambient conditions (i.e. 40°F and 90% relative humidity) with significant surface contamination, a 50:1 ratio (50 parts water to 1 part HoldTight®102) up to 100:1, depending on type of equipment and application procedure used (see manufacturer's detailed instructions) will normally protect the surface from flash rust for 48 hours or more -- providing the surface remains dry – and will remove virtually all loosely adhered surface contaminants, such as chlorides, sulfates, and other debris.

In a dry ambient setting a 100:1 mixture may be adequate. Note, however, that higher levels of surface contamination (e.g., chlorides and other soluble salts) will require higher concentrations of HoldTight ®102 at a given level of ambient air humidity

HoldTight®102 MSDS	issued	06/01/2010
	Supersedes	02/01/2010

When humidity is minimal, and the surfaces are not highly contaminated, HoldTight®102 has been effective in dilutions up to 250:1.

For use in any water or wet abrasive blast system with a 50 (water):1 (additive) injection system, pour HoldTight®102 undiluted into the inhibitor reservoir. Positively interlocked injector pumps (PIIP) will automatically provide a 50:1 ratio in the blasting water. To achieve a 100:1 mixture in the blast water in such systems, simply dilute HoldTight®102 with water 1:1 prior to pouring into the inhibitor reservoir. If no injection system is available, dilute HoldTight®102 with water as required prior to use.

Non-potable water (e.g., "plant" water) or any water with high levels of salt contamination will interfere with the performance of HoldTight®102 by re-contaminating the surface, causing flash rusting.

WARNING STATEMENT

CAUTION: May cause eye irritation.

PRECAUTIONARY MEASURES

Avoid contact with eyes. Avoid prolonged breathing of mist or vapor. Wash thoroughly after handling.

FIRST AID				
INGESTION:	None considered necessary			
INHALATION:	If irritation, headache, nausea, or drowsiness occu difficult or symptoms persist.	rs, remove to fresh air. Get r	nedical attention if breathing becomes	3
EYE CONTACT:	Flush eyes with water several times. Hold eyelids apart while flushing to rinse entire surface of eye and lids with water. Get medical attention if irritation persists.			
SKIN CONTACT: Wash skin with soap and water. Get medical attention if skin irritation develops or persists.				
FIRE:	In case of fire, use water, foam, dry chemical or CO)2.		
CHEMICAL/COMMON I Proprietary Formulated Non-Hazardous Materi	d Amine Compound	<u>RANGE IN %</u> 25.00 75.00		
<u>HMIS</u> Health: Flammability:	1 Reactivity: 0 0 Special: -	<u>NFPA</u> Health: 1 Flammability: 0	Reactivity: 0 Special: -	
DOT Proper Shipping I	Name: N.A., NOT REGULATED	DOT Hazardous Class:	N.A.	
CAUTION: Misuse of empty containers can be hazardous. Empty containers can be hazardous if used to store toxic, flammable, or reactive materials. Cutting or welding of empty containers might cause fire, explosion or toxic fumes from residues of other materials stored in them. Do not pressurize or expose to open flame or heat. Keep container closed and drum bungs in place.				of
Manufacturer:	HoldTight Solutions Inc., P.O. Box 27907, Houston, phone: 713.266.9339 / 800.319.8802 fax: 713.266.			

email info@holdtight.com web: www.holdtight.com